

Harlow Home Design Custom Home & Remodeling

Phone: 207-743-5753 Email: mharlow@harlowhomedesign.com

InSoFast EX 2.5 Foundation & Exterior Wall Insulation

InSoFast EX 2.5 (R-10) Insulation - Installed with No Drywall
(See Specifications below)

Optional Plus+ Wall Insulation:

If local code requires R-15 continuous foundation insulation, Plus+ Wall will exceed this requirement. It consists of 1-layer InSoFast EX 2.5 (R-10) & 1-layer Owens Corning Foamular (R-3) which is R-15.58 continuous, installed with NO drywall.

EX 2.5 Panel Features & Specifications:

Thickness	2.5"
Width x Height	2' x 4'
Continuous Closed-Cell Insulation	R-10
Comparable Performance to **	2x4 Wall/R-15 Batts
Fully Insulated Composite Studs (at 16" O.C.)	Recessed ½" Below Surface
Tongue and Groove Interlocking Edges	✓
Cutting Indicator Lines	✓
Electrical Raceways at Code Depth	✓
Drywall and Finish Ready	✓
Designed for Basements	✓
Moisture Drainage Channels on Back	✓
Qualifies as Continuous Insulation	✓
Nationwide Code Compliance (US & Canada) CCRR-1029	✓
Rain Screen Technology on Front	✓
Designed for Siding and Exterior Finishes	✓

EX 2.5 Panels



Installed Price

**Call for latest pricing
& Free Estimate**

**Call for latest pricing
& Free Estimate**

** Oak Ridge National Laboratory